







EI30 FD30 EITHER SIDE – CSTB RS14-090



3c Stability*



Smoke Seal S. Classification EN 13501-2 - BS EN 1634-3

Door Leaf

- Huet multi-layer acoustic core
- Thickness: 84mm hardwood stiles all round
- High stability leaf due to the inclusion of 4 steel sheets

Door Frame

- Hardwood
- Rebated monoblock frame
- Variety of widths
- Extension linings available
- Frame can be lacquered, stained or varnished
- Frame can be wrapped with wood veneer to match door leaf facings

Ironmongery

- 4 lift-off ball bearing hinges -190 x 80mm black
- Cut-outs/mortices are available to suit a variety of locks and handles
- Electric striking plate (available on single leaf)

Perimeter Seals

- Intumescent seals factory fitted (within the frame and leaf)
- Combined smoke and acoustic seals fitted within the frame and leaf
- Large thresholds selection



400x300

Choice of Door Facings

- Primed
- Wood veneers
- Laminated
- White paint finish + other colour available by request
- Grooved to a wide choice of standard and bespoke finishes

*Stability of the door leaf is an important factor, particularly in areas of temperature variance between rooms or between rooms and corridors. Any distortion of the door leaf will result in the seals not functioning correctly. With the inclusion of a minimum of 2 steel sheets and other materials, Huet door leafs offer less than 2mm of distortion. The result is a door leaf and seal which continues to perform even with wide temperature differences.




www.huet-doors.co.uk


Tel: +33 22 812 0413




















Pyramidal threshold 95x15




Mechanical drop seals




Flat threshold 80x12





Flat threshold 80x12



Pyramidal threshold 95x15

